

DECK FLASH BARRIER™



3"x75' Rolls
Part# DFB375

12"x25' Rolls
Part# DFB1225

**NEW
SUPER GRIP
ADHESIVE!**

PROTECT AND MAXIMIZE THE LIFE OF YOUR NEW DECK

SELF-ADHESIVE DECK, POST AND LEDGER BOARD FLASHING

APPLY **DECK FLASH BARRIER** TO TOPS OF JOISTS, AROUND POSTS AND OVER LEDGER BOARDS TO PROTECT AGAINST WOOD ROT AND WATER DAMAGE.

**PROTECTS GALVANIZED
METAL AND ALUMINUM
CONNECTORS FROM
CORROSION.**

**Easy to install, just peel
off release paper and
press in place.**



PREVENTS WOOD ROT

DECK FLASH BARRIER

DECK FLASH BARRIER is a flexible polyethylene waterproof flashing and barrier material, with a rubberized asphalt mastic adhesive.

DIRECTIONS FOR USE

INTENDED USES

JOIST, POST AND LEDGER BOARD PROTECTION:

When applied to the top of joists, around posts, and over ledger boards, Deck Flash Barrier creates a waterproof membrane that prevents wood rot and decay caused by moisture coming in contact with both treated and untreated lumber. Deck Flash Barrier's "Super Grip" rubberized asphalt adhesive self-seals around screws and nails, blocking a primary pathway for water infiltration into deck joists. By blocking moisture and preventing wood rot, Deck Flash Barrier maximizes the life of your new deck.

CORROSION BARRIER:

When Deck Flash Barrier is placed between ACQ, CA-B, or ACZA treated lumber and metal surfaces, such as galvanized metal and aluminum, it creates a physical barrier that prevents the corrosion of the metal surface caused by contact with the chemicals in treated lumber. It can be used to protect metal flashings and hangars at deck plates and sill plates, and anywhere treated lumber is used.

INSTALLATION

DECK JOISTS: Cut Deck Flash Barrier to the proper length. When applying to the tops and ends of deck joists, center over joist. Remove release paper and press in place. Firmly crease and fold Deck Flash Barrier over both sides of the joist. To maximize adhesion, roll with a small hand roller.

POSTS: When protecting posts, Deck Flash Barrier should be applied at the ground level with 2 to 3 inches extending above the finished grade. To determine the proper location on the post for product placement, insert the post in the hole, mark the post indicating the grade level, and then remove the post from the hole. To determine the proper length of Deck Flash Barrier to use, without removing the white release paper, wrap the material around the post, making sure that there is enough material for a minimum 3 inch overlap. Cut Deck Flash Barrier to proper length. Remove release paper and wrap around post while firmly pressing in

place. To maximize adhesion, roll with a small hand roller. To provide additional protection against deep standing water around the post, a bead of **non-silicone** caulk may be applied to the top edge of the Deck Flash Barrier.

LEDGER BOARDS: Twelve inch Deck Flash Barrier is recommended to provide ledger board protection. It should be installed with a minimum of 3 inches of material up the wall of the building, and a minimum of 3 inches of material down the face of the ledger board. Always make sure that on the wall of the building, Deck Flash Barrier is installed **under** the house wrap or weather resistive barrier. To maximize adhesion, roll with a small hand roller.

WARNINGS

1. Deck Flash Barrier should be applied to clean dry surfaces when temperatures are a minimum of 40°F or warmer.
2. If site conditions prevent proper adhesion, Deck Flash Barrier can be mechanically attached using staples or nails, or a construction grade spray adhesive can be used to increase adhesion.
3. Deck Flash Barrier is designed to be covered by either deck boards or siding, and should not be exposed to direct sunlight for more than 90 days.
4. Although Deck Flash Barrier has a slip-resistant surface, it may still be slippery. Extreme caution should be used when walking or standing on Deck Flash Barrier.

LIMITED WARRANTY: Cofair warrants this product to be of merchantable quality when used and/or applied in accordance with instructions hereon. Cofair does not warrant this product for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of defective product as purchased. THIS LIMITED WARRANTY IS ISSUED IN LIEU OF ALL OTHER EXPRESSED AND IMPLIED WARRANTIES, INCLUDING THE WARRANTY OF FITNESS, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.



Skokie, IL 60076
Phone: 800-333-6700
www.cofair.com

